



### Main

Product or component type	Actuator
Actuator type	Electric
Actuator product series	MZ20
Actuator model	MZ20
Product destination	Zone valves
Hold-in power consumption in VA	1 VA AC
Power loss return	Non-spring return
Control signal	Proportional/modulating
Targeted region	Europe Asia Pacific. Australia.

### Complementary

Actuator	Linear
Control type	Automatic reset
Rated supply voltage	24 V AC
Analogue input range	0...10 V DC
Stroke length	5.5 mm
Stroke auto calibration	False
Force N	200 N
Force lbf	45 lbf
Position indicator	Stem position cut out on yoke
Lead length	1.5 m
Connection valve	Coupling ring M30 x 1.5
Stroke running time	117 s

### Environment

IP degree of protection	IP43
Ambient air temperature for operation	-5...55 °C
Relative humidity	5...95 % non-condensing
Ambient air temperature for storage	-25...65 °C

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.0 cm
Package 1 Width	9.5 cm
Package 1 Length	12.0 cm
Package 1 Weight	259.0 g

## Offer Sustainability

EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>