



### Main

Product or component type	Actuator
Actuator type	Electric
Product destination	Globe valve
Actuator	Linear
Switch function	2 SPDT
Power loss return	Spring return
Control signal	Modulating
Force N	700 N
Force lbf	157 lbf
Stroke running time	102 s
IP degree of protection	IP54
Targeted region	Europe Asia Pacific.

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	21.0 cm
Package 1 Width	21.0 cm
Package 1 Length	29.0 cm
Package 1 Weight	5.822 kg

### Offer Sustainability

EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.