

# Product data sheet

## Characteristics

# A9A19804

## Acti9 IC60 RCBO - low level auxiliary contact - 1OF/SD Smartlink - 24V DC



### Main

Range of product	Acti9
Product or component type	OC or fault contact
Device short name	iOF+SD 24
Signal contacts composition	1 C/O
[In] rated current	2...100 mA at 24 V, DC
9 mm pitches	1

### Complementary

Local signalling	Mechanical indicator
Mounting mode	Clip-on
Mounting support	DIN rail
Height	86 mm
Width	9 mm
Depth	71 mm
Net weight	30 g
Colour	White
Connections - terminals	Spring-loaded terminal Ti241 cable(s) 0.5...1.5 mm <sup>2</sup> - rigid Spring-loaded terminal Ti241 cable(s) 0.5...1.5 mm <sup>2</sup> - flexible
Wire stripping length	10 mm

### Environment

Standards	EN/IEC 60947-5-1 EN/IEC 60947-5-4
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-40...70 °C

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.000 cm
Package 1 Width	8.000 cm
Package 1 Length	9.800 cm
Package 1 Weight	47.000 g
Unit Type of Package 2	S03
Number of Units in Package 2	72
Package 2 Height	30.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	4.259 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 <a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant with Exemptions
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>
RoHS exemption information	 Yes
Environmental Disclosure	 <a href="#">Product Environmental Profile</a>
Circularity Profile	 <a href="#">End Of Life Information</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins