



Main

Range	Acti9
Product or component type	Display
Device application	Human-machine dialogue application
Range compatibility	Acti9 Acti9 PowerTag Link smart communication module
Display type	LCD

Complementary

Display colour	Color
Display resolution	320 x 240 pixels QVGA
Display size	2 inch
Information displayed	Current Voltage Active power Power factor Energy consumption Alarms
Control type	4 x push-button
[Us] rated supply voltage	110...277 V AC 24 V DC
Power consumption in W	2.7 W
Connector type	Terminal block
Provided equipment	Power supply
Mounting mode	Rail Flush-mounted
Mounting support	DIN rail Framework
Width	72 mm
Height	95 mm
Embedding depth	49.5 mm
Projecting depth	18.5 mm
Net weight	137 g

Environment

IP degree of protection	IP41 conforming to IEC 60529 (on flush mounting)
Relative humidity	5...95 % at 45 °C
Operating altitude	0...2000 m
Ambient air temperature for operation	-25...60 °C
Ambient air temperature for storage	-40...85 °C
Standards	EN 61326 EN 300-328 EN 301-489-1 EN 301-489-17
Product certifications	CE

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.000 cm
Package 1 Width	8.000 cm
Package 1 Length	11.000 cm
Package 1 Weight	224.000 g
Unit Type of Package 2	S03
Number of Units in Package 2	27
Package 2 Height	30.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	6.445 kg
Unit Type of Package 3	P06
Number of Units in Package 3	216
Package 3 Height	75.000 cm
Package 3 Width	80.000 cm
Package 3 Length	60.000 cm
Package 3 Weight	59.560 kg

Offer Sustainability

REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes