



Main

Range	Acti9
Product or component type	Comb busbar
Mounting mode	Horizontal
Accessory / separate part category	Connection accessory
Lines description	1L + N
Length in 18 mm modules	48

Complementary

Number of ways	18 ways Aux + N + 1 L + Vigì
Poles configuration for 1 way	1 x 1P + N
Connection pitch	9 mm between phase and neutral
Connector type	Tooth
Distance between way	45 mm
Marking	N L
Insulation	Insulated
Device presentation	Cuttable
[Ie] rated operational current	80 A at 40 °C
[Ue] rated operational voltage	230 V AC Ph/N
[Ui] rated insulation voltage	400 V AC conforming to IEC 61439-1
[Uimp] rated impulse withstand voltage	4 kV
Mounting location	Top on tunnel type terminals
9 mm pitches	96
Height	29 mm
Width	862 mm
Depth	26 mm
Net weight	339 g
Colour	White (RAL 9003)
Range compatibility	Acti 9 Acti9 C40 Acti 9 Acti9 C40 Vigì Acti 9 Acti9 DT40 Acti 9 Acti9 DT40 Vigì Acti 9 Acti9 iDPN Acti 9 Acti9 iDPN Vigì Acti 9 Acti9 ID C40 Acti 9 Acti9 IDc Acti 9 Acti9 iTG40 Multi9 Multi9 N40 Vigì Acti9 Acti9 iC40 Acti9 Acti9 iDT40 Acti9 Acti9 iDD40 Acti9 Acti9 iDD40 TG Acti9 Vigì iTG40 Acti9 Acti9 iIG40 Acti9 Acti9 iCV40 Acti9 Vigì iCG40 Acti9 Acti9 iID40

The information provided in this documentation contains general descriptions and/or technical characteristics of the products of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

Standards	EN/IEC 60439-1
Fire resistance	960 °C (30 s) conforming to IEC 60695-2-1
Pollution degree	3 conforming to EN/IEC 60439-1
IP degree of protection	IP20 with end-pieces and tooth covers

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.500 cm
Package 1 Width	3.000 cm
Package 1 Length	83.000 cm
Package 1 Weight	330.000 g
Unit Type of Package 2	BB1
Number of Units in Package 2	5
Package 2 Height	9.800 cm
Package 2 Width	107.000 cm
Package 2 Length	9.800 cm
Package 2 Weight	1.773 kg
Unit Type of Package 3	P12
Number of Units in Package 3	100
Package 3 Height	45.000 cm
Package 3 Width	80.000 cm
Package 3 Length	120.000 cm
Package 3 Weight	46.460 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins