

Product data sheet

Characteristics

AG13A23A

Erie actuator, general purpose, 24VAC, Pop-Top mount on Erie VT valves, 2 position, 0.9m (36") lead, End switch



Main

Product or component type	Actuator
Actuator type	Electric
Actuator product series	AG
Product destination	Zone valves
Actuator	Rotary
Control type	Automatic reset
Switch function	1 SPST
Rated supply voltage	24 V AC
Transformer rated power in VA	7.5 VA
Power consumption in W	6.5 W
Power consumption in VA	7.5 VA AC
Power loss return	Spring return
Control signal	2-position (on/off)
Position indicator	Green push stem with color markers
Lead length	1 m
Leads and connections	Appliance
Spring return timing	9 s
IP degree of protection	IP53
Material	Aluminium: housing
Ambient air temperature for operation	0...40 °C
Relative humidity	5...95 % non-condensing
Ambient air temperature for storage	-40...71 °C
Targeted region	Europe Asia Pacific. Australia.

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.38 cm
Package 1 Width	5.38 cm
Package 1 Length	10.515 cm
Package 1 Weight	550.0 g

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes

