

Product data sheet

Characteristics

AH13U230

Erie actuator, high close off model, 230VAC,
Pop-Top mount on Erie VT valves, 2 position,
0.9m (36") lead



Main

Product or component type	Actuator
Actuator type	Electric
Actuator product series	AH
Product destination	Zone valves
Actuator	Rotary
Control type	Automatic reset
Switch function	No
Rated supply voltage	230 V AC
Transformer rated power in VA	7.5 VA
Power consumption in W	6.5 W
Power consumption in VA	7.5 VA AC
Power loss return	Spring return
Control signal	2-position (on/off)
Position indicator	Green push stem with color markers
Lead length	1 m
Leads and connections	Appliance
Spring return timing	9 s
IP degree of protection	IP53
Material	Aluminium: housing
Ambient air temperature for operation	0...40 °C
Relative humidity	5...95 % non-condensing
Ambient air temperature for storage	-40...71 °C
Targeted region	Europe Asia Pacific. Australia.

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.38 cm
Package 1 Width	5.38 cm
Package 1 Length	10.515 cm
Package 1 Weight	550.0 g

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile