



Overview

Lead time	Usually in Stock
-----------	------------------



Main

Colour	Black
Product or component type	PDU
PDU type	Basic
Cord length	3.66 m
Provided equipment	Installation guide Safety guide

Complementary

Input Voltage	200 V 230 V 240 V
Height	4.4 cm
Width	43.8 cm
Output Voltage	200 V 230 V 240 V
Depth	9.3 cm
Net weight	2.78 kg
Mounting location	Front Rear
Mounting preference	No preference
Input Plug Type	IEC 60309 32 A 2P + E
Mounting mode	Not rack-mountable
Rack units	1U
Mounting position	Horizontal
Permissible voltage	200...240 V
Max line current	32 A
Input current limits	32 A
Load capacity	7400 VA
Network frequency	50/60 Hz
Outlet type and quantity	4 IEC 60320 C19

Environment

Product certifications	CE[RETURN]IRAM[RETURN]VDE
------------------------	---------------------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	20.8 cm
Package 1 Width	18 cm
Package 1 Length	47.8 cm
Package 1 Weight	3.75 kg
SCC14	10731304327827

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant  EU RoHS Declaration
Lead free	Yes
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------