



Overview

Lead time	Usually in Stock
-----------	------------------



Main

Colour	Black
Product or component type	PDU
PDU type	Basic
Cord length	2.44 m
Provided equipment	Installation guide Rack mounting brackets

Complementary

Input Voltage	208 V 3 phases
Height	4.4 cm
Width	43.7 cm
Output Voltage	200 V 208 V
Depth	25.4 cm
Net weight	7.98 kg
Mounting location	Front Rear
Mounting preference	No preference
Mounting mode	Rack-mounted
Rack units	1U
Mounting position	Horizontal
[In] rated current	40 A
Input current limits	50 A
Load capacity	14400 VA
Network frequency	50/60 Hz
Number of input connectors	1 CS8365
Outlet type and quantity	6 IEC 60320 C19

Environment

Product certifications	cUL listed[RETURN]METI Denan[RETURN]UL listed
Standards	CSA C22.2 No. 60950-1-03 UL 60950-1
Ambient air temperature for operation	-5...45 °C
Relative humidity	5...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-25...65 °C
Storage Relative Humidity	5...95 %
Storage altitude	0.00...15240.00 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	24.1 cm
Package 1 Width	50.2 cm
Package 1 Length	55.9 cm
Package 1 Weight	10.1 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant  EU RoHS Declaration
Lead free	Yes
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------