



Overview

| | |
|-----------|------------------|
| Lead time | Usually in Stock |
|-----------|------------------|

Main

| | |
|---------------------------|---|
| Colour | Black |
| Product or component type | PDU |
| PDU type | Basic |
| Cord length | 3.05 m |
| Number of cables | 1 |
| Provided equipment | Installation guide Rack mounting brackets Toolless mounting kit |

Complementary

| | |
|--------------------------|-------------------------------------|
| Input Voltage | 200 V 208 V 230 V |
| Height | 161.9 cm |
| Width | 5.6 cm |
| Output Voltage | 230 V |
| Depth | 4.4 cm |
| Net weight | 4.86 kg |
| Mounting location | Side |
| Mounting preference | No preference |
| Input Plug Type | IEC 60320 C20 |
| Mounting mode | Rack-mounted |
| Rack units | 0U |
| Mounting position | Vertical |
| Input current limits | 16 A |
| Load capacity | 3680 VA |
| Network frequency | 50/60 Hz |
| Outlet type and quantity | 20 IEC 60320 C13 4 IEC 60320 C19 |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

| | |
|---------------------------------------|---------------------------------------|
| Product certifications | CE[RETURN]GOST[RETURN]IRAM[RETURN]VDE |
| Ambient air temperature for operation | 0...45 °C |
| Relative humidity | 5...95 % |
| Operating altitude | 0...10000 ft |
| Ambient air temperature for storage | -25...65 °C |
| Storage Relative Humidity | 5...95 % |
| Storage altitude | 0.00...15240.00 m |

Packing Units

| | |
|------------------------------|----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 212.1 cm |
| Package 1 Width | 15.2 cm |
| Package 1 Length | 12.7 cm |
| Package 1 Weight | 5.758 kg |

Offer Sustainability

| | |
|-----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Lead free | Yes |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End Of Life Information |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Optimized Energy Efficiency | Energy efficient product |
| Take-back | Take-back program available |

Contractual warranty

| | |
|----------|---------------------------|
| Warranty | 2 years repair or replace |
|----------|---------------------------|