



### Overview

Lead time	Usually in Stock
-----------	------------------

### Main

Colour	Black
Product or component type	PDU
PDU type	Basic
Cord length	1.83 m
Number of cables	1
Provided equipment	Installation guide Toolless mounting kit

### Complementary

Input Voltage	400 V 3 phases
Height	92.7 cm
Width	5.5 cm
Output Voltage	230 V
Depth	8.8 cm
Net weight	4.76 kg
Mounting location	Side
Mounting preference	No preference
Input Plug Type	IEC 60309 32 A 3P + N + PE
Mounting mode	Rack-mounted
Rack units	0U
Mounting position	Vertical
Permissible voltage	200...250 V
Max line current	32 A
Load capacity	22000 VA
Network frequency	47...63 Hz
Outlet type and quantity	3 IEC 60320 C13 6 IEC 60320 C19

## Environment

Product certifications	CE[RETURN]GOST[RETURN]VDE
Ambient air temperature for operation	-5...60 °C
Relative humidity	5...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-25...65 °C
Storage Relative Humidity	5...95 %
Storage altitude	0.00...15240.00 m

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	106.7 cm
Package 1 Width	29.8 cm
Package 1 Length	8.3 cm
Package 1 Weight	6.247 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 <a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant  <a href="#">EU RoHS Declaration</a>
Lead free	Yes
Environmental Disclosure	 <a href="#">Product Environmental Profile</a>
Circularity Profile	 <a href="#">End Of Life Information</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

## Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------