

Product data sheet

Characteristics

AP7568

Rack PDU, Basic, Zero U, 12.5kW, 208V, (30)C13,(6)C19; 3' Cord



Overview

Lead time	Usually in Stock
-----------	------------------

Main

Colour	Black
Product or component type	PDU
PDU type	Basic
Cord length	0.91 m
Number of cables	1
Provided equipment	Cord retention bracket(s) Documentation CD Installation guide Rack mounting brackets Toolless mounting kit

Complementary

Input Voltage	208 V 3 phases
Height	177.8 cm
Width	5.6 cm
Output Voltage	208 V
Depth	8.9 cm
Net weight	6.95 kg
Mounting location	Side
Mounting preference	No preference
Mounting mode	Rack-mounted
Rack units	0U
Mounting position	Vertical
Max line current	35 A
Input current limits	35 A
Load capacity	12500 VA
Network frequency	50/60 Hz
Number of input connectors	1 CS8365
Outlet type and quantity	30 IEC 60320 C13 6 IEC 60320 C19

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

Product certifications	cUL listed[RETURN]UL listed
Standards	CSA C22.2 No. 60950-1-03 UL 60950-1
Ambient air temperature for operation	-5...45 °C
Relative humidity	5...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-25...65 °C
Storage Relative Humidity	5...95 %
Storage altitude	0.00...15240.00 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	210.8 cm
Package 1 Width	12.7 cm
Package 1 Length	15.2 cm
Package 1 Weight	10.17 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant  EU RoHS Declaration
Lead free	Yes
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------