



Overview

Lead time	Usually in Stock
-----------	------------------



Main

Colour	Black
Product or component type	PDU
PDU type	Basic
Cord length	2.50 m
Number of cables	1
Provided equipment	User manual Rack mounting brackets

Complementary

Input Voltage	120 V 208 V 230 V
Height	4.4 cm
Width	44.7 cm
Output Voltage	120 V 208 V 230 V
Depth	5.7 cm
Net weight	0.98 kg
Mounting location	Front Rear
Mounting preference	No preference
Input Plug Type	IEC 60320 C20
Mounting mode	Rack-mounted
Rack units	1U
Mounting position	Horizontal
Permissible voltage	90...250 V
Max line current	16 A
Input current limits	16 A
Load capacity	3680 VA
Network frequency	50/60 Hz
Outlet type and quantity	10 IEC 60320 C13 2 IEC 60320 C19

Environment

Product certifications	cUL listed[RETURN]CE[RETURN]UL listed[RETURN]VDE[RETURN]Victoria
Ambient air temperature for operation	0...45 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-25...65 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.00...15240.00 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	16.5 cm
Package 1 Width	48.3 cm
Package 1 Length	15.2 cm
Package 1 Weight	2.355 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Lead free	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------