



Overview

| | |
|-----------|------------------|
| Lead time | Usually in Stock |
|-----------|------------------|



Main

| | |
|---------------------------|---|
| Colour | Black |
| Product or component type | PDU |
| PDU type | Basic |
| Cord length | 1.98 m |
| Number of cables | 1 |
| Provided equipment | Installation guide Rack mounting brackets Toolless mounting kit |

Complementary

| | |
|--------------------------|---|
| Input Voltage | 120 V 200 V 208 V 230 V 240 V |
| Height | 61 cm |
| Width | 4.4 cm |
| Output Voltage | 208 V 230 V |
| Depth | 4.4 cm |
| Net weight | 2 kg |
| Mounting location | Side |
| Mounting preference | No preference |
| Input Plug Type | IEC 60320 C14 |
| Mounting mode | Rack-mounted |
| Rack units | 0U |
| Mounting position | Vertical |
| Permissible voltage | 100...240 V |
| Input current limits | 10 A |
| Load capacity | 2300 VA |
| Network frequency | 50/60 Hz |
| Outlet type and quantity | 15 IEC 60320 C13 |

Environment

| | |
|---------------------------------------|--|
| Product certifications | cUL listed[RETURN]CE[RETURN]GOST[RETURN]Queensland Australia[RETURN]UL listed[RETURN]VDE |
| Ambient air temperature for operation | 0...45 °C |
| Relative humidity | 0...95 % |
| Operating altitude | 0...10000 ft |
| Ambient air temperature for storage | -25...65 °C |
| Storage Relative Humidity | 0...95 % |
| Storage altitude | 0.00...15240.00 m |

Packing Units

| | |
|------------------------------|----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 64.8 cm |
| Package 1 Width | 17.8 cm |
| Package 1 Length | 15.2 cm |
| Package 1 Weight | 2.724 kg |

Offer Sustainability

| | |
|-----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation |  REACH Declaration |
| EU RoHS Directive | Compliant  EU RoHS Declaration |
| Lead free | Yes |
| Environmental Disclosure |  Product Environmental Profile |
| Circularity Profile |  End Of Life Information |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Optimized Energy Efficiency | Energy efficient product |
| Take-back | Take-back program available |

Contractual warranty

| | |
|----------|---------------------------|
| Warranty | 2 years repair or replace |
|----------|---------------------------|