



Overview

Presentation	UPS management SmartSlot Card which supports the UPSLink protocol for SMT, SMX and SURTD Smart-UPS.
Lead time	Usually in Stock

Main

Product or component type	Communication card
Provided equipment	RS-232 configuration cable User manual

Physical

Colour	Black
Height	3.8 cm
Width	12.1 cm
Depth	11.4 cm
Net weight	0.08 kg
Mounting preference	No preference
Mounting mode	Not rack-mountable

Environmental

Ambient air temperature for operation	0...45 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-5...45 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.00...15240.00 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.1 cm
Package 1 Width	23.5 cm
Package 1 Length	15.9 cm
Package 1 Weight	0.339 kg
SCC14	10731304283215

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant  EU RoHS Declaration
Lead free	Yes
Environmental Disclosure	 Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------