



Overview

Lead time	Usually in Stock
-----------	------------------

Main

Product or component type	Replacement battery cartridge
Battery type	Lead-acid battery
Provided equipment	All required connectors Battery recycling guide Reusable packaging Installation guide

Batteries & Runtime

Number of battery blocks per string	2
Number of battery free slots	0
Number of battery filled slots	0
Device mounting	Enclosed battery cartridge
Battery voltage	24 V
Number of battery replacement quantity	1

Physical

Colour	Charcoal
Height	10.4 cm
Width	15.1 cm
Depth	13.2 cm
Net weight	5.58 kg
Mounting mode	Not rack-mountable

Output

Battery capacity	9.0 Ah
------------------	--------

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environmental

Ambient air temperature for operation	0...40 °C
Operating altitude	0...10000 ft
Relative humidity	0...95 %
Ambient air temperature for storage	0...40 °C
Storage altitude	0.00...3048.00 m
Storage Relative Humidity	0...95 %

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	30.5 cm
Package 1 Width	10.2 cm
Package 1 Length	22.9 cm
Package 1 Weight	6.14 kg
SCC14	10731304243561

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------