



Overview

Lead time	Usually in Stock
-----------	------------------

Main

Product or component type	Replacement battery cartridge
Main Output Voltage	24 V DC
Number of rack unit	0U
Battery type	VRLA

Batteries & Runtime

Battery location	Internal battery
Number of battery blocks per string	2
Number of battery free slots	0
Number of battery filled slots	0
Battery voltage	24 V
Number of battery replacement quantity	1

Physical

Height	64.8 mm
Width	150.9 mm
Depth	98.6 mm
Net weight	5 kg
Mounting mode	Rack-mounted
USB compatible	No

Output

Battery capacity	9 Ah
------------------	------

Conformance

Product certifications	CB
------------------------	----

Environmental

Ambient air temperature for operation	0...40 °C
Operating altitude	0...2000 m
Relative humidity	0...90 % non-condensing
Ambient air temperature for storage	-15...45 °C
Storage altitude	0...3000 m
Storage Relative Humidity	0...95 % non-condensing

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	28.5 cm
Package 1 Width	32.5 cm
Package 1 Length	16.5 cm
Package 1 Weight	5.8 kg
Unit Type of Package 2	PAM
Number of Units in Package 2	84
Package 2 Height	128 cm
Package 2 Width	100 cm
Package 2 Length	120 cm
Package 2 Weight	500.2 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

Contractual warranty

Warranty	2 Years
----------	---------