



Overview

Lead time	Usually in Stock
-----------	------------------

Main

Product or component type	Replacement battery cartridge
Main Output Voltage	48 V DC
Number of rack unit	0U
Battery type	VRLA

Batteries & Runtime

Battery location	Internal battery
Number of battery blocks per string	4
Number of battery free slots	0
Number of battery filled slots	0
Battery voltage	48 V
Number of battery replacement quantity	1

Physical

Height	130 mm
Width	151 mm
Depth	209 mm
Net weight	8 kg
Mounting mode	Not rack-mountable
USB compatible	No

Output

Battery capacity	7 Ah
------------------	------

Conformance

Product certifications	CB
------------------------	----

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environmental

Ambient air temperature for operation	0...40 °C
Operating altitude	0...3000 m
Relative humidity	0...95 % non-condensing
Ambient air temperature for storage	-15...40 °C
Storage altitude	0...3000 m
Storage Relative Humidity	10...95 % non-condensing

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	22.2 cm
Package 1 Width	22.8 cm
Package 1 Length	28.6 cm
Package 1 Weight	9.75 kg
Unit Type of Package 2	P06
Number of Units in Package 2	12
Package 2 Height	57.5 cm
Package 2 Width	60 cm
Package 2 Length	80 cm
Package 2 Weight	125.5 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

Contractual warranty

Warranty	2 Years
----------	---------