

Product data sheet

Characteristics

APCRBCV210

APC Replacement Battery Cartridge, VRLA, 7Ah, 12V DC, 2-year warranty



Overview

| | |
|-----------|------------------|
| Lead time | Usually in Stock |
|-----------|------------------|



Main

| | |
|---------------------------|-------------------------------|
| Product or component type | Replacement battery cartridge |
| Main Output Voltage | 12 V DC |
| Number of rack unit | 0U |
| Battery type | VRLA |

Batteries & Runtime

| | |
|--|------------------|
| Battery location | Internal battery |
| Number of battery blocks per string | 1 |
| Number of battery free slots | 0 |
| Number of battery filled slots | 0 |
| Battery voltage | 12 V |
| Number of battery replacement quantity | 1 |

Physical

| | |
|----------------|--------------------|
| Height | 99 mm |
| Width | 65 mm |
| Depth | 151 mm |
| Net weight | 1.84 kg |
| Mounting mode | Not rack-mountable |
| USB compatible | No |

Output

| | |
|------------------|------|
| Battery capacity | 7 Ah |
|------------------|------|

Conformance

| | |
|------------------------|----|
| Product certifications | CB |
|------------------------|----|

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or intended user to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environmental

| | |
|---------------------------------------|-------------------------|
| Ambient air temperature for operation | 0...40 °C |
| Operating altitude | 0...2000 m |
| Relative humidity | 0...90 % non-condensing |
| Ambient air temperature for storage | -15...45 °C |
| Storage altitude | 0...3000 m |
| Storage Relative Humidity | 0...95 % non-condensing |

Packing Units

| | |
|------------------------------|------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 17.000 cm |
| Package 1 Width | 15.500 cm |
| Package 1 Length | 18.700 cm |
| Package 1 Weight | 2.035 kg |
| Unit Type of Package 2 | BB1 |
| Number of Units in Package 2 | 6 |
| Package 2 Height | 18.700 cm |
| Package 2 Width | 39.000 cm |
| Package 2 Length | 49.000 cm |
| Package 2 Weight | 13.026 kg |
| Unit Type of Package 3 | P12 |
| Number of Units in Package 3 | 36 |
| Package 3 Height | 52.000 cm |
| Package 3 Width | 80.000 cm |
| Package 3 Length | 120.000 cm |
| Package 3 Weight | 88.000 kg |

Offer Sustainability

| | |
|----------------------------|--|
| Sustainable offer status | Green Premium product |
| REACH Regulation |  REACH Declaration |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information |  Yes |
| Environmental Disclosure |  Product Environmental Profile |
| Circularity Profile |  End Of Life Information |

Contractual warranty

| | |
|----------|---------|
| Warranty | 2 Years |
|----------|---------|