

Product data sheet

Characteristics

BJL26040

Circuit breaker, PowerPact B, 40A, 2 pole, 600Y/347VAC, 25kA, lugs, thermal magnetic, 80%



Main

| | |
|---------------------------|-----------------|
| Range | PowerPact |
| Product name | PowerPact B |
| Device short name | BJ 040 |
| Product or component type | Circuit breaker |
| Device application | Distribution |

Complementary

| | |
|---|---|
| [In] rated current | 40 A |
| Number of Poles | 2P |
| Control type | Toggle |
| Breaking capacity code | J |
| Breaking capacity | 100 KA at 208Y/120 V AC 50/60 Hz conforming to UL 489 100 KA at 240 V AC 50/60 Hz conforming to UL 489 65 KA at 480/277 V AC 50/60 Hz conforming to UL 489 65 KA at 480 V AC 50/60 Hz conforming to UL 489 25 KA at 600Y/347 V AC 50/60 Hz conforming to UL 489 50 kA at 250 V DC conforming to UL 489 |
| [Ue] rated operational voltage | 690 V AC 50/60 Hz conforming to UL 489 |
| Network frequency | 50/60 Hz |
| [Ics] rated service breaking capacity | 100 KA at 220...240 V AC 50/60 Hz conforming to IEC 60947-2 25 KA at 500...525 V AC 50/60 Hz conforming to IEC 60947-2 2.5 KA at 690 V AC 50/60 Hz conforming to IEC 60947-2 65 KA at 380...415 V AC 50/60 Hz conforming to IEC 60947-2 65 kA at 440 V AC 50/60 Hz conforming to IEC 60947-2 |
| [Uiimp] rated impulse withstand voltage | 8 kV conforming to IEC 60947-2 |
| Trip unit technology | Thermal-magnetic |
| Continuous current rating | 80 % |
| [Ui] rated insulation voltage | 800 V conforming to IEC 60947-2 |
| Suitability for isolation | Yes conforming to IEC 60947-2 |
| Utilisation category | Category A |
| Mechanical durability | 20000 cycles conforming to IEC 947-1 Annex K ed 5.2 |
| Electrical durability | 10000 cycles conforming to IEC 947-1 Annex K ed 5.2 at 440 V In |
| Connection pitch | 27 mm |
| AWG gauge | AWG 6...AWG 2/0 fine stranded aluminium/copper AWG 14...AWG 3/0 rigid or stranded aluminium/copper |
| Local signalling | Presence of auxiliary contacts: flag (green) |
| Mounting mode | Clip-on (35 x 15 mm symmetrical DIN rail) By screws (plate) |
| Electrical connection | Everlink lug, line Everlink lug, load |
| Tightening torque | 5 N.M for 2.5...16 mm ² (AWG 14...AWG 4) 9 N.m for 25...95 mm ² (AWG 3...AWG 3/0) |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

| | |
|-----------------------------|---|
| Number of slots | 1 slot(s) for auxiliary switch OF (plug-in) 1 slot(s) for voltage release MN or MX (plug-in) |
| Power wire stripping length | 20 mm |
| Color | Grey (RAL 7016) |
| 9 mm pitches | 6 |
| Height | 137 mm |
| Width | 54 mm |
| Depth | 80 mm |
| Net weight | 0.769 kg |
| Quantity per set | Set of 1 |
| Circuit breaker application | HACR rated |

Environment

| | |
|---------------------------------------|---|
| Quality labels | CE |
| Standards | EN/IEC 60947-5-1 UL 489 NEMA AB1 CSA C22.2 No 5 GB 14048.2 NMX J-266 EN/IEC 60947-2 |
| Product certifications | UL[RETURN]IEC[RETURN]CCC[RETURN]EAC[RETURN]CSA[RETURN]NOM |
| IP degree of protection | Front cover: IP40 conforming to IEC 60529 |
| IK degree of protection | IK07 conforming to IEC 62262 |
| Pollution degree | 3 conforming to IEC 60947-1 |
| Ambient air temperature for operation | -25...70 °C |
| Ambient air temperature for storage | -50...85 °C |
| Operating altitude | < 2000 m without derating 5000 m with derating |

Packing Units

| | |
|------------------------------|-----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 6.1 cm |
| Package 1 Width | 11.938 cm |
| Package 1 Length | 20.574 cm |
| Package 1 Weight | 680.389 g |

Offer Sustainability

| | |
|-----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation |  REACH Declaration |
| EU RoHS Directive | Compliant with Exemptions |
| Mercury free | Yes |
| China RoHS Regulation |  China RoHS Declaration |
| RoHS exemption information |  Yes |
| Environmental Disclosure |  Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| PVC free | Yes |
| Halogen content performance | Halogen free product |