



Main

Range of product	Modicon X80
Product or component type	CANopen communication module
Structure type	Open industrial fieldbus

Complementary

Product compatibility	M580 PLC
Physical interface	DB9 connector
Mode of transmission	NRZ
Transmission support medium	Profibus DP twisted shielded pairs cable
Transmission rate	9.6 kbit/s, 1200 m bus 19.2 kbit/s, 1200 m bus 93.75 kbit/s, 1200 m bus 187.5 kbit/s, 1000 m bus 500 kbit/s, 400 m bus 1.5 Mbit/s, 200 m bus 3 Mbit/s, 100 m bus 12 Mbit/s, 100 m bus
Number of server device(s)	63
Communication service	Implicit exchange of process data - 20...70 °C
Integrated connection type	Profibus DP - 1 SUB-D 9-pin female for Profibus DP
[Us] rated supply voltage	24 V DC internal
Current consumption	70 mA
Module format	Standard

Environment






Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-45...85 °C
Relative humidity	10...95 %
Operating altitude	<= 2000 m
Protective treatment	Conformal coating
Directives	2014/35/EU - low voltage directive 2014/30/EU - electromagnetic compatibility 2014/34/EU - ATEX directive
Product certifications	CE[RETURN]UL[RETURN]CSA[RETURN]RCM[RETURN]EAC[RETURN]Merchant Navy[RETURN]ATEX zone 2/22[RETURN]IECEx zone 2/22

Standards	EN/IEC 61131-2 EN/IEC 61010-2-201 UL 61010-2-201 CSA C22.2 No 61010-2-201 IACS E10 EN/IEC 61000-6-5, interface type 1 and type 2 EN/IEC 61850-3, location G EN/IEC 60079-0
Environmental characteristic	Gas resistant class Gx conforming to ISA S71.04 Gas resistant class 3C4 conforming to IEC 60721-3-3 Dust resistant class 3S4 conforming to IEC 60721-3-3 Sand resistant class 3S4 conforming to IEC 60721-3-3 Salt resistant level 2 conforming to IEC 68252 Mold growth resistant class 3B2 conforming to IEC 60721-3-3 Fungal spore resistant class 3B2 conforming to IEC 60721-3-3 Hazardous location class I division 2

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.500 cm
Package 1 Width	11.300 cm
Package 1 Length	11.800 cm
Package 1 Weight	194.000 g
Unit Type of Package 2	S02
Number of Units in Package 2	15
Package 2 Height	15.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	3.234 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins