BMENOS0300C

Network Option Switch with conformal coating





Main

| Range of product | Modicon X80 | |
|---------------------------|------------------|--|
| Product or component type | Switch module | |
| Product compatibility | BMEXBP backplane | |

Complementary

| [Us] rated supply voltage | 24 V for back plane | |
|-----------------------------|---|--|
| Power consumption in W | 3.3 W at 135 mA 25 °C 4.5 W at 185 mA 60 °C | |
| Number of port | 3 | |
| Integrated connection type | Ethernet/IP for device network Ethernet/IP for service port | |
| Communication port protocol | EtherNet/IP | |
| Local signalling | 1 LED (green) for module active (RUN) 1 LED (red) for module error (ERR) 1 LED (green/red) for module status (Mod Status) 1 LED (green/red) for network communication status (Net Status) | |
| Module format | Standard | |

| Environment | |
|---------------------------------------|---|
| Marking | CE |
| Directives | 2014/35/EU - low voltage directive 2014/30/EU - electromagnetic compatibility 2014/34/EU - ATEX directive |
| Product certifications | CE[RETURN]UL[RETURN]CSA[RETURN]RCM[RETURN]EAC[RETURN]Merchant Navy[RETURN]ATEX zone 2/22[RETURN]IECEx zone 2/22 |
| Standards | EN/IEC 61131-2 EN/IEC 61010-2-201 UL 61010-2-201 CSA C22.2 No 61010-2-201 IACS E10 EN/IEC 61000-6-5, interface type 1 and type 2 EN/IEC 61850-3, location G EN/IEC 60079-0 |
| Environmental characteristic | Gas resistant class Gx conforming to ISA S71.04 Gas resistant class 3C4 conforming to IEC 60721-3-3 Dust resistant class 3S4 conforming to IEC 60721-3-3 Sand resistant class 3S4 conforming to IEC 60721-3-3 Salt resistant level 2 conforming to IEC 68252 Mold growth resistant class 3B2 conforming to IEC 60721-3-3 Fungal spore resistant class 3B2 conforming to IEC 60721-3-3 Hazardous location class I division 2 |
| IP degree of protection | IP20 |
| Ambient air temperature for operation | 060 °C |
| Ambient air temperature for storage | -4085 °C |
| Operating altitude | <= 2000 m |
| Maximum altitude transport | 3000 m |

| Overvoltage category | II |
|----------------------|---------------------------|
| Relative humidity | 95 % without condensation |
| Protective treatment | Conformal coating |

Packing Units

| Unit Type of Package 1 | PCE |
|------------------------------|-----------|
| Number of Units in Package 1 | 1 |
| Package 1 Height | 5.800 cm |
| Package 1 Width | 11.200 cm |
| Package 1 Length | 12.200 cm |
| Package 1 Weight | 264.000 g |
| Unit Type of Package 2 | S02 |
| Number of Units in Package 2 | 5 |
| Package 2 Height | 15.000 cm |
| Package 2 Width | 30.000 cm |
| Package 2 Length | 40.000 cm |
| Package 2 Weight | 1.636 kg |

Offer Sustainability

| Sustainable offer status | Green Premium product |
|----------------------------|---|
| REACh Regulation | ☑ REACh Declaration |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS Declaration |
| RoHS exemption information | ₫Yes |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End Of Life Information |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |