

Product data sheet

Characteristics

C103MG040

Trip unit TM40G, ComPacT NSX100/160, 3 poles, thermal magnetic protections, generator protection, 40A rating



Main

| | |
|--------------------------------|--|
| Range | ComPacT new generation |
| Range of product | ComPacT NSX100...250 new generation ComPacT NSX100...250 DC new generation |
| Product or component type | Trip unit |
| Trip unit name | TM-G |
| Trip unit technology | Thermal-magnetic |
| Range compatibility | ComPacT new generation NSX100 ComPacT new generation NSX160 ComPacT new generation NSX100 DC |
| Device application | Generator |
| Poles description | 3P |
| Protected poles description | 3D |
| Trip unit protection functions | LI |
| Protection type | L : for overload protection (thermal) I : for short-circuit protection (magnetic) |
| Trip unit rating | 40 A at 40 °C |
| [Ue] rated operational voltage | 690 V AC 50/60 Hz 750 V DC |
| Network type | AC DC |
| Network frequency | 50/60 Hz |
| Circuit breaker mounting mode | Fixed |

Complementary

| | |
|---|---------------------------|
| Long-time pick-up adjustment type Ir (thermal protection) | Adjustable |
| [Ir] long-time protection pick-up adjustment range | 0.7...1 x In |
| Long-time protection delay adjustment type tr | Fixed |
| [tr] long-time protection delay adjustment range | 120...400 s at 1.5 x In |
| Instantaneous protection pick-up adjustment type li | Fixed |
| [li] instantaneous protection pick-up adjustment range | 80 A |
| Earth-leakage protection | Without |

Environment

| | |
|---------------------------------------|------------------------------|
| Standards | EN/IEC 60947-2 |
| Electrical shock protection class | Class II |
| Pollution degree | 3 conforming to IEC 60947-1 |
| IP degree of protection | IP40 conforming to IEC 60529 |
| Ambient air temperature for operation | -25...70 °C |
| Ambient air temperature for storage | -50...85 °C |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Packing Units

| | |
|------------------------------|----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 6.8 cm |
| Package 1 Width | 10.0 cm |
| Package 1 Length | 11.4 cm |
| Package 1 Weight | 441.0 g |
| Unit Type of Package 2 | S03 |
| Number of Units in Package 2 | 28 |
| Package 2 Height | 30.0 cm |
| Package 2 Width | 30.0 cm |
| Package 2 Length | 40.0 cm |
| Package 2 Weight | 12.75 kg |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation |  REACH Declaration |
| EU RoHS Directive | Compliant with Exemptions |
| Mercury free | Yes |
| China RoHS Regulation |  China RoHS Declaration |
| RoHS exemption information |  Yes |
| Environmental Disclosure |  Product Environmental Profile |
| Circularity Profile |  End Of Life Information |