

C10W32M100

Circuit breaker, ComPacT NSX100HB2,
100kA/690VAC, 3 poles, MicroLogic 2.2M trip
unit 100A



Main

| | |
|--|---|
| Range | ComPacT new generation |
| Product name | ComPacT NSX new generation |
| Device short name | NSX100HB2 |
| Product or component type | Circuit breaker |
| Device application | Motor protection |
| Poles description | 3P |
| Protected poles description | 3D |
| [In] rated current | 100 A at 65 °C |
| [Ue] rated operational voltage | 690 V AC 50/60 Hz |
| Network type | AC |
| Network frequency | 50/60 Hz |
| Suitability for isolation | Yes conforming to EN/IEC 60947-2 |
| Utilisation category | Category A |
| [Icu] rated ultimate short-circuit breaking capacity | 100 KA Icu at 500 V AC 50/60 Hz conforming to IEC 60947-2 100 KA Icu at 525 V AC 50/60 Hz conforming to IEC 60947-2 100 kA Icu at 660/690 V AC 50/60 Hz conforming to IEC 60947-2 |
| Performance level | HB2 100 kA 690 V AC |
| Trip unit name | MicroLogic 2.2 M |
| Trip unit technology | Electronic |
| Trip unit protection functions | LSol |
| Control type | Toggle |
| Circuit breaker mounting mode | Fixed |

Complementary

| | |
|---|---|
| [Ui] rated insulation voltage | 800 V AC 50/60 Hz |
| [Uimp] rated impulse withstand voltage | 8 kV |
| [Ics] rated service short-circuit breaking capacity | 100 KA at 500 V AC 50/60 Hz conforming to IEC 60947-2 100 KA at 525 V AC 50/60 Hz conforming to IEC 60947-2 100 kA at 660/690 V AC 50/60 Hz conforming to IEC 60947-2 |
| Mechanical durability | 20000 cycles |
| Electrical durability | 20000 Cycles at 440 V In/2 10000 Cycles at 440 V In 10000 Cycles at 690 V In/2 5000 cycles at 690 V In |
| Power dissipation per pole | 4.7 W |
| Mounting support | Backplate |
| Mounting position | Horizontal and vertical Flat on the back |
| Upside connection | Front |
| Downside connection | Front |
| Connection pitch | 35 mm |

| | |
|---|--|
| Protection type | L : for overload protection (long time) So : for short time short-circuit protection with fixed delay I : for instantaneous short-circuit protection |
| Trip unit rating | 100 A at 65 °C |
| Motor tripping class | 10 5 20 |
| Complementary motor protection | Phase unbalance |
| Long-time pick-up adjustment type Ir (thermal protection) | Adjustable 9 settings |
| [Ir] long-time protection pick-up adjustment range | 50...100 A |
| Long-time protection delay adjustment type tr | Fixed |
| [tr] long-time protection delay adjustment range | 120 S at 1.5 x Ir for trip class 5 6.5 S at 6 x Ir for trip class 5 5 S at 7.2 x Ir for trip class 5 240 S at 1.5 x Ir for trip class 10 13.5 S at 6 x Ir for trip class 10 10 S at 7.2 x Ir for trip class 10 480 S at 1.5 x Ir for trip class 20 26 S at 6 x Ir for trip class 20 20 s at 7.2 x Ir for trip class 20 |
| Thermal memory | 20 minutes before and after tripping |
| Short-time protection pick-up adjustment type Isd | Adjustable 9 settings |
| [Isd] Short-time protection pick-up adjustment range | 5...13 x Ir |
| Short-time protection delay adjustment type tsd | Fixed |
| Instantaneous protection pick-up adjustment type Ii | Fixed |
| [Ii] instantaneous protection pick-up adjustment range | 1500 A |
| Earth-leakage protection | Without |
| Zone selective interlocking ZSI | Without |
| Number of slots for electrical auxiliaries | 5 slot(s) |
| Local signalling | Flashing LED (green) for ready to operate LED 95 % Ith (red) for temperature over set point |
| Width (W) | 105 mm |
| Height (H) | 161 mm |
| Depth (D) | 86 mm |
| Net weight | 2.05 kg |

Environment

| | |
|---------------------------------------|--|
| Standards | EN/IEC 60947 |
| Product certifications | EAC[RETURN]CCC[RETURN]Marine |
| Overvoltage category | Class II |
| Electrical shock protection class | Class II |
| Pollution degree | 3 conforming to IEC 60664-1 |
| IP degree of protection | IP40 conforming to IEC 60529 |
| IK degree of protection | IK07 conforming to IEC 62262 |
| Ambient air temperature for operation | -25...70 °C |
| Ambient air temperature for storage | -50...85 °C |
| Relative humidity | 0...95 % |
| Operating altitude | 0...2000 m without derating 2000 m...5000 m with derating |

Packing Units

| | |
|------------------------------|---------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 14.0 cm |
| Package 1 Width | 11.0 cm |
| Package 1 Length | 20.0 cm |
| Package 1 Weight | 1.8 kg |
| Unit Type of Package 2 | S03 |

| | |
|------------------------------|---------|
| Number of Units in Package 2 | 4 |
| Package 2 Height | 30.0 cm |
| Package 2 Width | 30.0 cm |
| Package 2 Length | 40.0 cm |
| Package 2 Weight | 7.2 kg |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant with Exemptions |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS Declaration |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End Of Life Information |