



**Main**

|  |  |
|--|--|
| Range  | ComPacT new generation   |
| Product name   | ComPacT NSX new generation   |
| Device short name                                    | NSX250F  |
| Product or component type                            | Basic frame  |
| Device application                                   | Distribution   |
| Poles description                                    | 3P   |
| [In] rated current                                   | 250 A at 40 °C   |
| [Ue] rated operational voltage                       | 690 V AC 50/60 Hz conforming to IEC 60947-2  |
| Network type   | AC   |
| Network frequency                                    | 50/60 Hz   |
| Suitability for isolation                            | Yes conforming to EN/IEC 60947-2   |
| Utilisation category                                 | Category A   |
| [Icu] rated ultimate short-circuit breaking capacity | 85 KA at 240 V AC 50/60 Hz conforming to UL 508<br>22 KA Icu at 525 V AC 50/60 Hz conforming to IEC 60947-2<br>35 KA Icu at 440 V AC 50/60 Hz conforming to IEC 60947-2<br>36 KA Icu at 380/415 V AC 50/60 Hz conforming to IEC 60947-2<br>8 KA Icu at 660/690 V AC 50/60 Hz conforming to IEC 60947-2<br>85 KA Icu at 220/240 V AC 50/60 Hz conforming to IEC 60947-2<br>35 KA at 480 V AC 50/60 Hz conforming to UL 508<br>30 KA Icu at 500 V AC 50/60 Hz conforming to IEC 60947-2<br>15 kA at 600 V AC 50/60 Hz conforming to UL 508 |
| Performance level                                    | F 36 kA 415 V AC   |
| Control type   | Toggle   |
| Mounting mode  | Fixed  |

**Complementary**

|   |   |
|---|---|
| [Ui] rated insulation voltage                       | 800 V AC 50/60 Hz conforming to IEC 60947-2   |
| [Uimp] rated impulse withstand voltage              | 8 kV conforming to IEC 60947-2  |
| [Ics] rated service short-circuit breaking capacity | 35 KA at 440 V AC 50/60 Hz conforming to IEC 60947-2<br>36 KA at 380/415 V AC 50/60 Hz conforming to IEC 60947-2<br>85 KA at 220/240 V AC 50/60 Hz conforming to IEC 60947-2<br>22 KA at 525 V AC 50/60 Hz conforming to IEC 60947-2<br>30 KA at 500 V AC 50/60 Hz conforming to IEC 60947-2<br>8 kA at 660/690 V AC 50/60 Hz conforming to IEC 60947-2 |
| Mechanical durability                               | 20000 cycles conforming to IEC 60947-2  |
| Electrical durability                               | 10000 Cycles 440 V AC 50/60 Hz In conforming to IEC 60947-2<br>10000 Cycles 690 V AC 50/60 Hz In/2 conforming to IEC 60947-2<br>20000 Cycles 440 V AC 50/60 Hz In/2 conforming to IEC 60947-2<br>5000 cycles 690 V AC 50/60 Hz In conforming to IEC 60947-2   |
| Mounting support                                    | Backplate   |
| Upside connection                                   | Front   |
| Downside connection                                 | Front   |
| Connection pitch                                    | 35 mm   |
| Protection type                                     | Without protection  |

|            |        |
|------------|--------|
| Width (W)  | 105 mm |
| Height (H) | 161 mm |
| Depth (D)  | 86 mm  |

## Environment

|                                       |                              |
|---------------------------------------|------------------------------|
| Standards                             | EN/IEC 60947-2<br>UL 508     |
| Product certifications                | CSA[RETURN]UL                |
| Pollution degree                      | 3 conforming to IEC 60664-1  |
| IP degree of protection               | IP40 conforming to IEC 60529 |
| IK degree of protection               | IK07 conforming to IEC 62262 |
| Ambient air temperature for operation | -25...70 °C                  |
| Ambient air temperature for storage   | -50...85 °C                  |

## Packing Units

|                              |           |
|------------------------------|-----------|
| Unit Type of Package 1       | PCE       |
| Number of Units in Package 1 | 1         |
| Package 1 Height             | 14 cm     |
| Package 1 Width              | 11.2 cm   |
| Package 1 Length             | 19.2 cm   |
| Package 1 Weight             | 1.58 kg   |
| Unit Type of Package 2       | S03       |
| Number of Units in Package 2 | 7         |
| Package 2 Height             | 30 cm     |
| Package 2 Width              | 30 cm     |
| Package 2 Length             | 40 cm     |
| Package 2 Weight             | 11.434 kg |
| Unit Type of Package 3       | P12       |
| Number of Units in Package 3 | 56        |
| Package 3 Height             | 42.5 cm   |
| Package 3 Width              | 80 cm     |
| Package 3 Length             | 120 cm    |
| Package 3 Weight             | 107 kg    |

## Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product   |
| REACH Regulation           |  <a href="#">REACH Declaration</a>             |
| EU RoHS Directive          | Compliant with Exemptions   |
| Mercury free               | Yes   |
| China RoHS Regulation      |  <a href="#">China RoHS Declaration</a>        |
| RoHS exemption information |  <a href="#">Yes</a>                           |
| Environmental Disclosure   |  <a href="#">Product Environmental Profile</a> |
| Circularity Profile        |  <a href="#">End Of Life Information</a>       |