



### Main

|                                       |                           |
|---------------------------------------|---------------------------|
| Range compatibility                   | Harmony XVM Optimum       |
| Accessory / separate part category    | Lighting accessory        |
| Accessory / separate part type        | Super bright LED          |
| Accessory / separate part destination | Beacon and indicator bank |
| Bulb base                             | BA 15d                    |
| Signalling type                       | Flashing                  |
| Signalling colour                     | Orange                    |
| [Us] rated supply voltage             | 24 V AC/DC                |
| Luminance                             | 900 cd/m <sup>2</sup>     |
| Sale per indivisible quantity         | 1                         |

### Complementary

|                    |          |
|--------------------|----------|
| Flashing frequency | 1 Hz     |
| Net weight         | 0.009 kg |

### Packing Units

|                              |         |
|------------------------------|---------|
| Unit Type of Package 1       | PCE     |
| Number of Units in Package 1 | 1       |
| Package 1 Height             | 6.0 cm  |
| Package 1 Width              | 3.5 cm  |
| Package 1 Length             | 3.5 cm  |
| Package 1 Weight             | 14.0 g  |
| Unit Type of Package 2       | S01     |
| Number of Units in Package 2 | 100     |
| Package 2 Height             | 15 cm   |
| Package 2 Width              | 15 cm   |
| Package 2 Length             | 40 cm   |
| Package 2 Weight             | 1.6 kg  |
| Unit Type of Package 3       | P06     |
| Number of Units in Package 3 | 3200    |
| Package 3 Height             | 75 cm   |
| Package 3 Width              | 40 cm   |
| Package 3 Length             | 80 cm   |
| Package 3 Weight             | 69.8 kg |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product   |
| REACH Regulation           | <a href="#">REACH Declaration</a>   |
| REACH free of SVHC         | Yes   |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>                              |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>  |
| RoHS exemption information | <a href="#">Yes</a>   |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>   |
| Circularity Profile        | No need of specific recycling operations  |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|