



Overview

Presentation	Battery breaker kit that controls DC voltage sent from third party battery solutions to the UPS. For use with the Easy UPS 3S empty battery cabinet (E3SEBC7).
Lead time	Usually Ships within 6 Weeks

Main

Product or component type	Kit
Battery type	VRLA

Batteries & Runtime

Number of battery filled slots	0
Number of battery free slots	0

Physical

Height	43 cm
Width	27 cm
Depth	24 cm
Net weight	8 kg

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...3333 ft
Ambient air temperature for storage	-15...40 °C
Storage Relative Humidity	0...95 % non-condensing
Storage altitude	0.00...15240.00 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	43 cm
Package 1 Width	24 cm
Package 1 Length	27 cm
Package 1 Weight	8 kg

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes