ENN47942

Mureva FIX - installation tie - 194x9 mm - 100 pieces





Main

Product range	Mureva FIX	
Product type	Installation tie	
Colour tint	Black	
Quantity per set	100 pieces	

Complementary

Minimum tightening diameter	10 mm	
Maximum tightening diameter	42 mm	
Resistance to tearing	Resistance to tearing: 36 daN Ø 20 mm	
Material	PA (polyamide) 12 Rislan®	
Length	194 mm	
Width	9 mm	
Net weight	0.003 kg	

Environment

Maximum humidity absorption	0.9 %	
Operating temperature	-6085 °C 100 °C during 1000 hours 120 °C maximum	
Flame retardance	HB conforming to UL 94	
Standards	EN 50146	
Environmental characteristic	UV resistant	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.5 cm
Package 1 Width	10.5 cm
Package 1 Length	20.5 cm
Package 1 Weight	3.0 g
Unit Type of Package 2	BB1
Number of Units in Package 2	100
Package 2 Height	8.5 cm
Package 2 Width	10.5 cm
Package 2 Length	20.5 cm
Package 2 Weight	1.3 kg
Unit Type of Package 3	CAR
Number of Units in Package 3	2000
Package 3 Height	33.0 cm

Package 3 Width	35.0 cm
Package 3 Length	39.5 cm
Package 3 Weight	6.28 kg
Offer Sustainability	
Sustainable offer status	Green Premium product
REACh Regulation	[™] REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EVEL RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Circularity Profile

Warranty	18 months	

No need of specific recycling operations