

Product data sheet

Characteristics

ENN47992

Mureva FIX - installation tie - 370x9 mm - 100 pieces



Main

Product range	Mureva FIX
Product type	Installation tie
Colour tint	Black
Quantity per set	100 pieces

Complementary

Minimum tightening diameter	55 mm
Maximum tightening diameter	92 mm
Resistance to tearing	Resistance to tearing: 45 daN Ø 26 mm
Material	PA (polyamide) 12 Rislan®
Length	370 mm
Width	9 mm
Net weight	0.005 kg

Environment

Maximum humidity absorption	0.9 %
Operating temperature	-60...85 °C 100 °C during 1000 hours 120 °C maximum
Flame retardance	HB conforming to UL 94
Standards	EN 50146
Environmental characteristic	UV resistant

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	0.2 cm
Package 1 Width	0.9 cm
Package 1 Length	37 cm
Package 1 Weight	5 g

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Contractual warranty

Warranty	18 months
----------	-----------