

Product data sheet

Characteristics

EPDU1216S

Easy Rack PDU, Switched, 0U, 3 Phase, 11kW, 230V, 16A, 21 C13 and 6 C19 outlets, IEC60309 3P + N + PE inlet



Overview

Lead time Usually in Stock



Main

Colour	Black
Product or component type	PDU
PDU type	Switched
Number of cables	1

Complementary

Input Voltage	400 V 3 phases
Height	1794 mm
Width	55 mm
Output Voltage	230 V
Depth	62 mm
Net weight	6.2 kg
Mounting location	Side
Mounting preference	No preference
Input Plug Type	IEC 60309 16 A 3P + N + PE
Mounting position	Vertical
Input current limits	16 mA
Load capacity	11 kW
Network frequency	50/60 Hz
Plug standard	IEC 60309
Outlet type and quantity	21 IEC 60320 C13 6 IEC 60320 C19

Environment

Product certifications	CE[RETURN]EAC[RETURN]RCM[RETURN]TÜV
Ambient air temperature for operation	-5...45 °C
Relative humidity	5...95 %
Operating altitude	0...3000 m
Ambient air temperature for storage	-25...65 °C
Storage Relative Humidity	5...95 %
Storage altitude	0...15000 m

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.95 cm
Package 1 Width	16 cm
Package 1 Length	11 cm
Package 1 Weight	7.78 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	1 year repair or replace
----------	--------------------------