

HMIST6400SL

SpaceLogic Operator Display, 7" HMI for monitoring plant and zone controllers, BACnet / IP, panel-mounted in equipment room



Main

Net weight	0.8 kg
Directives	2014/35/EU - low voltage directive 2014/30/EU - electromagnetic compatibility
Width	208 mm
Product or component type	Touch panel screen
Product certifications	CE[RETURN]UL
Height	153 mm
Ambient air temperature for storage	-20...60 °C
Depth	45 mm
Enclosure material	PC
Display type	Colour TFT LCD
Display size	7 inch
Ambient air temperature for operation	0...50 °C
Display resolution	800 x 480 pixels WVGA
Communication port support	ETHERNET 10/100BASE
[Us] rated supply voltage	24 V DC +/- 20 %
Standards	EN 61000-6-4 EN 61000-6-2 EN 61131-2 UL 61010-2-201 IEC 61326-1
Relative humidity	10...90 % non-condensing
Product brand	Schneider Electric
Range of product	Operator Display ST6

Complementary

Brightness	16 levels
Front material	Aluminium
Inrush current	30 A
Power consumption in W	9 W
Display colour	16 million colours
Character font	ASCII ASCII (European characters)
Supply	External supply
Immunity to microbreaks	2 ms
Marking	CE EAC UL
Touch panel	Single touch analogue resistive
Local signalling	Status LED green Status LED orange Status LED red Buzzer
Cut-out dimensions	190 x 135 mm panel cut dimension

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Integrated connection type	1 COM1 serial link - 1 SUB-D 9-pin female - RS232C (rate: 2400...115200 bps)bottom 1 COM2 serial link - female RJ45 - RS485 (rate: 2400...115200 bps)back COM2 serial link (rate: 2400...187500 bps)back 1 USB 2.0 type Abottom 1 USB 2.0 type micro B 2 Ethernet
Fixing mode	By 2 screws, mounting on 1.6..5 mm thick panel conforming to UL 61010-2-201 By 2 screws conforming to EN 61131-2 By 2 screws conforming to IEC 61000-6-2
Realtime clock	Built-in 0...50 °C Built-in 10...90 % RH
Backlight lifespan	50000 hours with white




Environment

Operating altitude	2000 m
Vibration resistance	+/- 3.5 mm (f = 5...9 Hz) X, Y, Z directions for 10 cycles (approx. 100 min) conforming to EN/IEC 61131-2 9.8 m/s ² (f = 9...150 Hz)
Shock resistance	147 m/s ² for 11 ms (X, Y, Z directions for 3 times) conforming to EN/IEC 61131-2
NEMA degree of protection	NEMA 4 front panel (indoor use) NEMA 13 front panel (in enclosure)
IP degree of protection	IP20 (rear panel) conforming to IEC 61131-2 IP65 (front panel) conforming to IEC 61131-2

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9.4 cm
Package 1 Width	18.0 cm
Package 1 Length	27.0 cm
Package 1 Weight	1.028 kg

Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins