



Main

Range of product	PacDrive 3
Product or component type	Connector module
Accessory / separate part category	Connection accessories
Device short name	ILM

Complementary

[Us] rated supply voltage	250...700 V
[Uc] control circuit voltage	24 V DC (tolerance: - 20...25 %)
Input current	20 A
Control threshold overvoltage	860 V
Output current	20 A
Peak output current	40 A
Physical interface	SERCOS III
Type of cooling	Natural convection
Overvoltage category	Class 3 conforming to IEC 61800-5-1
Width	44.5 mm
Height	310 mm
Depth	270 mm
Net weight	3 kg

Environment

IP degree of protection	IP20
Pollution degree	2 conforming to IEC 61800-5-1

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	11.500 cm
Package 1 Width	33.500 cm
Package 1 Length	44.500 cm
Package 1 Weight	2.835 kg
Unit Type of Package 2	P06
Number of Units in Package 2	10
Package 2 Height	75.000 cm
Package 2 Width	60.000 cm
Package 2 Length	80.000 cm
Package 2 Weight	41.350 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information
PVC free	Yes