



### Main

Range of product	PacDrive 3
Product or component type	Distribution block
Device short name	ILM

### Complementary

[Us] rated supply voltage	250...700 V
[Uc] control circuit voltage	24 V DC (tolerance: - 20...25 %)
Input current	20 A
Physical interface	SERCOS III, transmission rate: 100 Mbit/s
Type of cooling	Natural convection
Oversupply category	Class 3 conforming to IEC 61800-5-1
Material	Polycarbonate
Width	230 mm
Height	94 mm
Depth	151.4 mm
Net weight	0.85 kg

### Environment

IP degree of protection	IP65
Pollution degree	2 conforming to IEC 61800-5-1

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	10.2 cm
Package 1 Width	32.5 cm
Package 1 Length	42.5 cm
Package 1 Weight	1.73 kg
Unit Type of Package 2	S06
Number of Units in Package 2	10
Package 2 Height	75.0 cm
Package 2 Width	80.0 cm
Package 2 Length	60.0 cm
Package 2 Weight	25.0 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 <a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>
RoHS exemption information	 Yes
Environmental Disclosure	 <a href="#">Product Environmental Profile</a>
Circularity Profile	 <a href="#">End Of Life Information</a>
PVC free	Yes