



### Main

Range	Vigilohm
Device short name	IM20-1700
Product or component type	Network adaptor subassembly
Device application	Medium network
Range compatibility	Vigilohm Vigilohm IM IM20 insulation monitoring device Vigilohm Vigilohm IM IM20L insulation monitoring device

### Complementary

Network rated voltage	600...1700 V - AC (neutral distributed) 440...1000 V - AC (neutral not distributed) 345...1000 V - DC
Average impedance	400 kOhm
Maximum distance to	IM20: 3 m
Net weight	0.2 kg

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8 cm
Package 1 Width	8 cm
Package 1 Length	9.5 cm
Package 1 Weight	150 g
Unit Type of Package 2	S03
Number of Units in Package 2	36
Package 2 Height	30 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	6.018 kg

### Offer Sustainability

REACH Regulation	<input checked="" type="checkbox"/> <a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	<input checked="" type="checkbox"/> <a href="#">China RoHS Declaration</a>
RoHS exemption information	<input checked="" type="checkbox"/> Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

### Contractual warranty

Warranty	18 months
----------	-----------