

# Product data sheet

## Characteristics

# KBA40ZFSU

Cable suspension system, Canalis KBA, 25/40A, bracket with steel cable, steel cable supplied, galvanized version



### Main

Range of product	Canalis
Product or component type	Bracket
Product compatibility	KBA
Fixing device mounting	Universal fixing bracket and steel cable
Maximum load	60 kg
Quantity per set	Set of 10

### Complementary

Accessory / separate part category	Fixing accessory
Width	39 mm
Depth	22 mm
Net weight	105 g

### Environment

Standards	IEC 61439-6
-----------	-------------

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.000 cm
Package 1 Width	18.000 cm
Package 1 Length	23.000 cm
Package 1 Weight	120.000 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	7.000 cm
Package 2 Width	20.000 cm
Package 2 Length	22.000 cm
Package 2 Weight	1.200 kg
Unit Type of Package 3	CAR
Number of Units in Package 3	50
Package 3 Height	20.000 cm
Package 3 Width	20.000 cm
Package 3 Length	40.000 cm
Package 3 Weight	6.400 kg

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Offer Sustainability

Sustainable offer status	Green Premium product
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration
Environmental Disclosure	 Product Environmental Profile

## Contractual warranty

Warranty	18 months
----------	-----------