

KBA40ZFU

Universal fixing bracket, Canalis KBA,
25/40A, suspended on threaded rod or lateral,
galvanized version



Main

Range of product	Canalis
Product or component type	Bracket
Product compatibility	KBA
Fixing device mounting	Suspended on threaded rod
Maximum load	60 kg

Complementary

Accessory / separate part category	Fixing accessory
------------------------------------	------------------

Environment

Standards	IEC 61439-6
-----------	-------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.000 cm
Package 1 Width	3.800 cm
Package 1 Length	7.000 cm
Package 1 Weight	33.000 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	4.000 cm
Package 2 Width	14.500 cm
Package 2 Length	11.000 cm
Package 2 Weight	336.000 g
Unit Type of Package 3	CAR
Number of Units in Package 3	200
Package 3 Height	18.000 cm
Package 3 Width	24.500 cm
Package 3 Length	38.000 cm
Package 3 Weight	7.100 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
PVC free	Yes
Halogen content performance	Halogen free product

Contractual warranty

Warranty	18 months
----------	-----------