

Product data sheet

Characteristics

KBB40ABG44T2W

End feed unit, Canalis KBB, 40A, left mounting, 2 circuits, 3L+N+PE, with 2 optional remote control circuits, RAL9003



Main

Range of product	Canalis
Device short name	KBB
Product compatibility	Canalis KBB busbar trunking 25...40 A
Product or component type	Feed unit
Conductors material	Aluminium
[Ie] rated operational current	40 A
[Ue] rated operational voltage	230...400 V
Number of circuits	2
Busbar trunking polarity	3L + N + PE L + N + PE
Protection type	Without protection
Control type	Remote control
Colour	White (RAL 9003)

Complementary

Provided equipment	End cover
Mounting location	Left
Mounting mode	By clips
Mounting support	Busbar
Connections - terminals	Terminal block - Pg 21 for 6...10 mm ²
Width	244 mm
Depth	103.5 mm
Height	75.5 mm
Net weight	400 g
Standards	IEC 61439-6

Environment

IP degree of protection	IP55 conforming to IEC 60529
-------------------------	------------------------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.55 cm
Package 1 Width	10.35 cm
Package 1 Length	24.4 cm
Package 1 Weight	600.0 g

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
PVC free	Yes
Halogen content performance	Halogen free product

Contractual warranty

Warranty	18 months
----------	-----------