

# KEF05F

KE Series Flow Meter, R<sup>3</sup>/<sub>4</sub> Threaded Brass,  
2.5 m<sup>3</sup>/h Nominal, Flow Meter



## Main

Range of product	KE Series
Product or component type	Flow meter
Type of measurement	Flow
Device application	Energy metering Sub-metering
Location	Plant room
Device composition	Keypad
Calibration certificate	Yes
Colour	Off white
Depth	48 mm
Height	76 mm
Net weight	1.2 kg
Width	190 mm
Display type	LCD
Enclosure material	Thermoplastic, PC 10 % GF with TPE
Energy units	L M3
Field programmable	Yes
Fitting material	Brass
Fitting size	G1B (R3/4)
Fitting type	Threaded
Flow measurement accuracy	+/- 2 %
Flow measurement range	0.025...5 m3/h
Sensor type	Ultrasonic sensor flow Thermistor temperature
[Ui] rated insulation voltage	3.75 kV
IP degree of protection	IP65
Controlled fluid	Water
Meter location	Flow line
Operating fluid temperature	2...130 °C
Relative humidity	0...100 % RH, non-condensing
Ambient air temperature for operation	5...55 °C
Output type	Analog
Pipe material	Metallic Polymer
Network frequency	50 Hz 60 Hz
Pressure rating	PN16
Standards	EN 1434 class A (MID Class E1) EN 1434 class C (MID Class E2)
Storage Relative Humidity	0...100 % RH, non-condensing
Ambient air temperature for storage	-25...60 °C

[Us] rated supply voltage	230 V AC 24 V AC 161...264 V AC 12...36 V AC
Temperature measurement accuracy	+/- 4 %
Measurement temperature	2...130 °C

### Complementary

Totalizer quantities	1
Function available	Logging Totalizer resetable
Maximum power consumption in W	1 W
Pressure drop	0.14 bar
Maximum sensing distance	190 mm
Display resolution	7 digits
Clamping connection capacity	<= 1 mm <sup>2</sup>

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	21.0 cm
Package 1 Width	24.6 cm
Package 1 Length	24.5 cm
Package 1 Weight	1.2 kg