


KRA1250ZC5

Edgewise zed unit, Canalis KRA, aluminium, 1250A, 3L+N°PE, made to measure, grey RAL7030



Main

Range	Canalis
Product name	KR
Product or component type	Zed elbow
Device short name	KRA
Product specific application	Enterprise data centres Healthcare Water and waste water Oil and gas Real estate and office buildings Mining minerals and metals
Device application	Change direction
Material	Aluminium
[Ie] rated operational current	1250 A at 35 °C
Polarity	3L + N + PE
Earth conductor	Standard earth
Short-circuit level	Standard version

Complementary

Housing material	Mineral epoxy resin
Contacts material	Tinned aluminium
[Ue] rated operational voltage	1000 V
Network frequency	50/60 Hz
[Ui] rated insulation voltage	1000 V
[Icw] rated short-time withstand current	53 kA
[Ipk] rated peak withstand current	117 kA
Radiated magnetic field	14.68 mT
Thermal stress limit	2809000 kA².s
Maximum voltage drop	<0.0102 V with power factor = 1 at 50 Hz with 1A for 100 m long <0.013 V with power factor = 0.9 at 50 Hz with 1A for 100 m long <0.0134 V with power factor = 0.8 at 50 Hz with 1A for 100 m long <0.0133 V with power factor = 0.7 at 50 Hz with 1A for 100 m long
Linear resistance	L: R20 20 °C= 0.048 mΩ/m L: R1 35 °C= 0.059 mΩ/m at Inc and 50 Hz L: X1 35 °C= 0.05 mΩ/m at Inc and 50 Hz L: Z1 35 °C= 0.079 mΩ/m at Inc and 50 Hz L - PE: R0 20 °C= 0.159 mΩ/m symmetrical components method L - PE: X0 20 °C= 0.284 mΩ/m symmetrical components method L - PE: Z0 20 °C= 0.325 mΩ/m symmetrical components method L-N: R0 20 °C= 0.119 mΩ/m symmetrical components method L-N: X0 20 °C= 0.118 mΩ/m symmetrical components method L-N: Z0 20 °C= 0.167 mΩ/m symmetrical components method
Mounting location	Indoor Outdoor
Product certifications	ATEX[RETURN]CE[RETURN]EAC
Standards	IEC 61439-6
Width	120 mm
Height	130 mm
Colour	Grey (RAL 7030)

Length	Direction 1: 350...700 mm Direction 2: 10...700 mm Direction 3: 350...700 mm
Linear load	40 kg/m

Environment

IP degree of protection	IP68 conforming to IEC 60529
IK degree of protection	IK10 conforming to IEC 62262
Pollution degree	3
Fire resistance	760 °C 180 min conforming to IEC 60331-1
Derating factor	0...35 °C (100 % of In) 35...40 °C (96 % of In) 40...45 °C (89 % of In) 45...50 °C (84 % of In) 50...55 °C (78 % of In)
Operating altitude	1000 m 100 % of In (indoor) 2000 m 99 % of In (indoor) 3000 m 96 % of In (indoor) 4000 m 90 % of In (indoor) 1000 m 98 % of In (outdoor) 2000 m 94 % of In (outdoor) 3000 m 89 % of In (outdoor) 4000 m 83 % of In (outdoor)
Environmental characteristic	EMC directive conforming to IEC 61439-6

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	40.0 cm
Package 1 Width	50.0 cm
Package 1 Length	50.0 cm
Package 1 Weight	58.8 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Halogen free product