

Product data sheet

Characteristics

KRA3200FT520

Straight feeder length, Canalis KR, aluminium, 3200A, 3L+N+PE, fire rated, made to measure length 1.5m-2m, grey RAL7030



Main

| | |
|--------------------------------|---|
| Range | Canalis |
| Product name | KR |
| Product or component type | Busbar trunking |
| Busbar description | Transport length Fire rated |
| Device short name | KRA |
| Product specific application | Oil and gas Healthcare Real estate and office buildings Mining minerals and metals Enterprise data centres Water and waste water |
| Device application | Feeder length |
| Material | Aluminium |
| [Ie] rated operational current | 3200 A at 35 °C |
| Polarity | 3L + N + PE |
| Number of tap-off outlets | 0 |
| Earth conductor | Standard earth |
| Short-circuit level | Standard version |
| Length | 1501...2000 mm |

Complementary

| | |
|--|--|
| Housing material | Mineral epoxy resin |
| Contacts material | Tinned aluminium |
| [Ue] rated operational voltage | 1000 V |
| Network frequency | 50/60 Hz |
| [Ui] rated insulation voltage | 1000 V |
| [Icw] rated short-time withstand current | 100 kA |
| [Ipk] rated peak withstand current | 220 kA |
| Radiated magnetic field | 37.09 mT |
| Thermal stress limit | 10000000 kA ² .s |
| Maximum voltage drop | <0.0033 V with power factor = 1 at 50 Hz with 1A for 100 m long <0.0048 V with power factor = 0.9 at 50 Hz with 1A for 100 m long <0.0051 V with power factor = 0.8 at 50 Hz with 1A for 100 m long <0.0053 V with power factor = 0.7 at 50 Hz with 1A for 100 m long |
| Mounting location | Indoor Outdoor |
| Installation direction | Horizontal Vertical |
| Product certifications | CE[RETURN]ATEX[RETURN]EAC |
| Standards | IEC 61439-1 IEC 61439-6 |
| Dimension type | Made to measure |
| Width | 160 mm |
| Height | 500 mm |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

| | |
|-------------|-----------------|
| Colour | Grey (RAL 7030) |
| Linear load | 113 kg/m |

Environment

| | |
|------------------------------|---|
| IP degree of protection | IP68 conforming to IEC 60529 |
| IK degree of protection | IK10 conforming to IEC 62262 |
| Pollution degree | 3 |
| Fire resistance | 1000 °C 90 min conforming to DIN 4102-12 2000 |
| Derating factor | 0...35 °C (100 % of In) 35...40 °C (96 % of In) 40...45 °C (89 % of In) 45...50 °C (84 % of In) 50...55 °C (78 % of In) |
| Operating altitude | 1000 m 100 % of In (indoor) 2000 m 99 % of In (indoor) 3000 m 96 % of In (indoor) 4000 m 90 % of In (indoor) 1000 m 98 % of In (outdoor) 2000 m 94 % of In (outdoor) 3000 m 89 % of In (outdoor) 4000 m 83 % of In (outdoor) |
| Environmental characteristic | EMC directive conforming to IEC 61439-6 |

Packing Units

| | |
|------------------------------|----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 50.0 cm |
| Package 1 Width | 16.0 cm |
| Package 1 Length | 200.0 cm |
| Package 1 Weight | 237.3 kg |

Offer Sustainability

| | |
|-----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation |  REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant  EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| China RoHS Regulation |  China RoHS Declaration |
| RoHS exemption information |  Yes |
| Environmental Disclosure |  Product Environmental Profile |
| Circularity Profile |  End Of Life Information |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Halogen content performance | Halogen free product |