
KRB0270FM10

Fire rated casting mould, Canalis KR, 2500A for KRA, 3200A for KRC, for junction blocks, 3/4 conductors





Main

Range	Canalis
Product name	KR
Product or component type	Casting mould
Device short name	KRB
Range compatibility	Canalis KR KRA Canalis KR KRC
Accessory / separate part category	Coupling accessory
[le] rated operational current	2000 A with aluminium 2500 A with copper
Busbar trunking polarity	3L + N or 3L + PE or 3L + PEN 3L
Length	360 mm

Complementary

Width	180 mm
Height	350 mm
Quantity per set	Set of 1
Kit composition	8 x neoprene seal 2 x mould 2 x C-profile

Packing Units

3		
Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	27.0 cm	
Package 1 Width	10.0 cm	
Package 1 Length	30.0 cm	
Package 1 Weight	17.01 kg	

Offer Sustainability

[™] REACh Declaration
REACT Declaration
Yes
Compliant [☑] EU RoHS Declaration
Yes
Yes
☑ China RoHS Declaration
₽¥Yes
Product Environmental Profile
End Of Life Information

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not inherent or and is not to be used for determining suitability or inhability of these products for specific user applications. It is the dourn aren in integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Halogen free product