



## Main

|                                |                                         |
|--------------------------------|-----------------------------------------|
| Range                          | Canalis                                 |
| Product name                   | KT                                      |
| Product or component type      | Straight feeder trunking                |
| Device short name              | KTA                                     |
| Device application             | Feeder length                           |
| Supply                         | Switchboard<br>Oil-immersed transformer |
| Material                       | Aluminium                               |
| [Ie] rated operational current | 800 A at 35 °C                          |
| Neutral position               | Left                                    |
| Earth conductor                | Reinforced                              |
| Short-circuit level            | Standard version                        |
| Provided equipment             | Trunking unit                           |

## Complementary

|                                          |                                                                                                                                                                                                                                                                                |
|------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Housing material                         | Polyester film                                                                                                                                                                                                                                                                 |
| Contacts material                        | Copper                                                                                                                                                                                                                                                                         |
| [Ue] rated operational voltage           | 1000 V                                                                                                                                                                                                                                                                         |
| Network frequency                        | 50/60 Hz                                                                                                                                                                                                                                                                       |
| [Ui] rated insulation voltage            | 1000 V                                                                                                                                                                                                                                                                         |
| [Icw] rated short-time withstand current | 31 kA                                                                                                                                                                                                                                                                          |
| [Ipk] rated peak withstand current       | 64 kA                                                                                                                                                                                                                                                                          |
| Radiated magnetic field                  | 0.4 µT                                                                                                                                                                                                                                                                         |
| Thermal stress limit                     | 961000 kA <sup>2</sup> .s                                                                                                                                                                                                                                                      |
| THDI                                     | 0...15 % 800 A<br>15...33 % 1000 A<br>33...100 % 1250 A                                                                                                                                                                                                                        |
| Maximum voltage drop                     | <0.0083 V with power factor = 1 at 50 Hz with 1A for 100 m long<br><0.0081 V with power factor = 0.9 at 50 Hz with 1A for 100 m long<br><0.0076 V with power factor = 0.8 at 50 Hz with 1A for 100 m long<br><0.0069 V with power factor = 0.7 at 50 Hz with 1A for 100 m long |
| Mounting mode                            | By screws                                                                                                                                                                                                                                                                      |
| Mounting support                         | Plate                                                                                                                                                                                                                                                                          |
| Polarity                                 | 3L + N + PER                                                                                                                                                                                                                                                                   |
| Number of tap-off outlets                | 0                                                                                                                                                                                                                                                                              |
| Standards                                | IEC 61439-1<br>IEC 61439-6                                                                                                                                                                                                                                                     |
| Dimension type                           | Made to measure                                                                                                                                                                                                                                                                |
| Connection pitch                         | 80...250 mm                                                                                                                                                                                                                                                                    |
| Depth                                    | 230 mm                                                                                                                                                                                                                                                                         |
| Height                                   | Direction 1: 235...734 mm                                                                                                                                                                                                                                                      |
| Colour                                   | White (RAL 9001)                                                                                                                                                                                                                                                               |
| Linear load                              | 13 kg/m                                                                                                                                                                                                                                                                        |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Environment

|                         |                                                                                                                                     |
|-------------------------|-------------------------------------------------------------------------------------------------------------------------------------|
| IP degree of protection | IP55 conforming to IEC 60529                                                                                                        |
| IK degree of protection | IK08 conforming to IEC 62262                                                                                                        |
| Derating factor         | 0...35 °C (100 % of In)<br>35...40 °C (97 % of In)<br>40...45 °C (93 % of In)<br>45...50 °C (90 % of In)<br>50...55 °C (86 % of In) |

## Packing Units

|                              |         |
|------------------------------|---------|
| Unit Type of Package 1       | PCE     |
| Number of Units in Package 1 | 1       |
| Package 1 Height             | 45.0 cm |
| Package 1 Width              | 23.0 cm |
| Package 1 Length             | 95.0 cm |
| Package 1 Weight             | 15.0 kg |

## Offer Sustainability

|                            |                                                                                                                             |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                                                       |
| REACH Regulation           | <a href="#">REACH Declaration</a>                                                                                           |
| REACH free of SVHC         | Yes                                                                                                                         |
| EU RoHS Directive          | Compliant <a href="#">EU RoHS Declaration</a>                                                                               |
| Toxic heavy metal free     | Yes                                                                                                                         |
| Mercury free               | Yes                                                                                                                         |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>                                                                                      |
| RoHS exemption information | <a href="#">Yes</a>                                                                                                         |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>                                                                               |
| Circularity Profile        | <a href="#">End Of Life Information</a>                                                                                     |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |