

# KTA3200EL32

Feed unit for dry type transformers, Canalis  
KTA, aluminium, 3200A, 3L+PE, made to  
measure, neutral N2, white RAL9001



## Main

|                                |                      |
|--------------------------------|----------------------|
| Range                          | Canalis              |
| Product name                   | KT                   |
| Product or component type      | Side feeder trunking |
| Device short name              | KTA                  |
| Device application             | Feeder length        |
| Supply                         | Dry-type transformer |
| Material                       | Aluminium            |
| [Ie] rated operational current | 3200 A at 35 °C      |
| Neutral position               | Left                 |
| Earth conductor                | Standard earth       |
| Short-circuit level            | Standard version     |
| Provided equipment             | Trunking unit        |

## Complementary

|                                          |                                                                                                                                                                                                                                                                                |
|------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Housing material                         | Polyester film                                                                                                                                                                                                                                                                 |
| Contacts material                        | Copper                                                                                                                                                                                                                                                                         |
| [Ue] rated operational voltage           | 1000 V                                                                                                                                                                                                                                                                         |
| Network frequency                        | 50/60 Hz                                                                                                                                                                                                                                                                       |
| [Ui] rated insulation voltage            | 1000 V                                                                                                                                                                                                                                                                         |
| [Icw] rated short-time withstand current | 86 kA                                                                                                                                                                                                                                                                          |
| [Ipk] rated peak withstand current       | 189 kA                                                                                                                                                                                                                                                                         |
| Radiated magnetic field                  | 2.1 µT                                                                                                                                                                                                                                                                         |
| Thermal stress limit                     | 7396000 kA².s                                                                                                                                                                                                                                                                  |
| THDI                                     | 0...15 % 3200 A<br>15...33 % 4000 A                                                                                                                                                                                                                                            |
| Maximum voltage drop                     | <0.0018 V with power factor = 1 at 50 Hz with 1A for 100 m long<br><0.0019 V with power factor = 0.9 at 50 Hz with 1A for 100 m long<br><0.0018 V with power factor = 0.8 at 50 Hz with 1A for 100 m long<br><0.0017 V with power factor = 0.7 at 50 Hz with 1A for 100 m long |
| Mounting mode                            | By screws                                                                                                                                                                                                                                                                      |
| Mounting support                         | Plate                                                                                                                                                                                                                                                                          |
| Polarity                                 | 3L + PE                                                                                                                                                                                                                                                                        |
| Number of tap-off outlets                | 0                                                                                                                                                                                                                                                                              |
| Standards                                | IEC 61439-6<br>IEC 61439-1                                                                                                                                                                                                                                                     |
| Dimension type                           | Made to measure                                                                                                                                                                                                                                                                |
| Connection pitch                         | 470...700 mm                                                                                                                                                                                                                                                                   |
| Bar width                                | 200 mm                                                                                                                                                                                                                                                                         |
| Depth                                    | 140 mm                                                                                                                                                                                                                                                                         |
| Height                                   | 324 mm                                                                                                                                                                                                                                                                         |
| Length                                   | 1900 mm                                                                                                                                                                                                                                                                        |
| Colour                                   | White (RAL 9001)                                                                                                                                                                                                                                                               |
| Linear load                              | 31 kg/m                                                                                                                                                                                                                                                                        |

## Environment

|                         |                                                                                                                                     |
|-------------------------|-------------------------------------------------------------------------------------------------------------------------------------|
| IP degree of protection | IP55 conforming to IEC 60529                                                                                                        |
| IK degree of protection | IK08 conforming to IEC 62262                                                                                                        |
| Derating factor         | 0...35 °C (100 % of In)<br>35...40 °C (97 % of In)<br>40...45 °C (93 % of In)<br>45...50 °C (90 % of In)<br>50...55 °C (86 % of In) |

## Packing Units

|                              |          |
|------------------------------|----------|
| Unit Type of Package 1       | PCE      |
| Number of Units in Package 1 | 1        |
| Package 1 Height             | 50.0 cm  |
| Package 1 Width              | 13.8 cm  |
| Package 1 Length             | 190.0 cm |
| Package 1 Weight             | 55.75 kg |

## Offer Sustainability

|                             |                                                                                                                             |
|-----------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status    | Green Premium product                                                                                                       |
| REACH Regulation            | <a href="#">REACH Declaration</a>                                                                                           |
| REACH free of SVHC          | Yes                                                                                                                         |
| EU RoHS Directive           | Compliant <a href="#">EU RoHS Declaration</a>                                                                               |
| Toxic heavy metal free      | Yes                                                                                                                         |
| Mercury free                | Yes                                                                                                                         |
| China RoHS Regulation       | <a href="#">China RoHS Declaration</a>                                                                                      |
| RoHS exemption information  | <a href="#">Yes</a>                                                                                                         |
| Environmental Disclosure    | <a href="#">Product Environmental Profile</a>                                                                               |
| Circularity Profile         | <a href="#">End Of Life Information</a>                                                                                     |
| WEEE                        | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| PVC free                    | Yes                                                                                                                         |
| Halogen content performance | Halogen free product                                                                                                        |