


# KTA4000EL53

Feed unit for dry type transformers, Canalis KTA, aluminium, 4000A, 3L+N+PER, made to measure, neutral N3, white RAL9001



## Main

|                                |                        |
|--------------------------------|------------------------|
| Range                          | Canalis                |
| Product name                   | KT                     |
| Product or component type      | Center feeder trunking |
| Device short name              | KTA                    |
| Device application             | Feeder length          |
| Supply                         | Dry-type transformer   |
| Material                       | Aluminium              |
| [Ie] rated operational current | 4000 A at 35 °C        |
| Neutral position               | Right                  |
| Earth conductor                | Reinforced             |
| Short-circuit level            | Standard version       |
| Provided equipment             | Trunking unit          |

## Complementary

|                                          |                                                                                                                                                                                                                                                                                |
|------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Housing material                         | Polyester film                                                                                                                                                                                                                                                                 |
| Contacts material                        | Copper                                                                                                                                                                                                                                                                         |
| [Ue] rated operational voltage           | 1000 V                                                                                                                                                                                                                                                                         |
| Network frequency                        | 50/60 Hz                                                                                                                                                                                                                                                                       |
| [Ui] rated insulation voltage            | 1000 V                                                                                                                                                                                                                                                                         |
| [Icw] rated short-time withstand current | 90 kA                                                                                                                                                                                                                                                                          |
| [Ipk] rated peak withstand current       | 198 kA                                                                                                                                                                                                                                                                         |
| Radiated magnetic field                  | 3 µT                                                                                                                                                                                                                                                                           |
| Thermal stress limit                     | 8100000 kA².s                                                                                                                                                                                                                                                                  |
| THDI                                     | 0...15 % 4000 A                                                                                                                                                                                                                                                                |
| Maximum voltage drop                     | <0.0015 V with power factor = 1 at 50 Hz with 1A for 100 m long<br><0.0016 V with power factor = 0.9 at 50 Hz with 1A for 100 m long<br><0.0015 V with power factor = 0.8 at 50 Hz with 1A for 100 m long<br><0.0015 V with power factor = 0.7 at 50 Hz with 1A for 100 m long |
| Mounting mode                            | By screws                                                                                                                                                                                                                                                                      |
| Mounting support                         | Plate                                                                                                                                                                                                                                                                          |
| Polarity                                 | 3L + N + PER                                                                                                                                                                                                                                                                   |
| Number of tap-off outlets                | 0                                                                                                                                                                                                                                                                              |
| Standards                                | IEC 61439-1<br>IEC 61439-6                                                                                                                                                                                                                                                     |
| Dimension type                           | Made to measure                                                                                                                                                                                                                                                                |
| Connection pitch                         | 470...700 mm                                                                                                                                                                                                                                                                   |
| Bar width                                | 200 mm                                                                                                                                                                                                                                                                         |
| Depth                                    | 140 mm                                                                                                                                                                                                                                                                         |
| Height                                   | 664 mm                                                                                                                                                                                                                                                                         |
| Length                                   | Direction 1: 260 mm<br>1680 mm                                                                                                                                                                                                                                                 |
| Colour                                   | White (RAL 9001)                                                                                                                                                                                                                                                               |
| Linear load                              | 45 kg/m                                                                                                                                                                                                                                                                        |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Environment

|                         |                                                                                                                                     |
|-------------------------|-------------------------------------------------------------------------------------------------------------------------------------|
| IP degree of protection | IP55 conforming to IEC 60529                                                                                                        |
| IK degree of protection | IK08 conforming to IEC 62262                                                                                                        |
| Derating factor         | 0...35 °C (100 % of In)<br>35...40 °C (97 % of In)<br>40...45 °C (93 % of In)<br>45...50 °C (90 % of In)<br>50...55 °C (86 % of In) |

## Packing Units

|                              |          |
|------------------------------|----------|
| Unit Type of Package 1       | PCE      |
| Number of Units in Package 1 | 1        |
| Package 1 Height             | 68.0 cm  |
| Package 1 Width              | 13.8 cm  |
| Package 1 Length             | 190.0 cm |
| Package 1 Weight             | 70.4 kg  |