



Main

Range	Canalis
Product name	KT
Product or component type	Braid
Device short name	KTB
Accessory / separate part category	Connection accessory
Busbar cross section	100 x 6 mm
Length	400 mm

Complementary

[Ie] rated operational current	800 A with 1 braid(s) 1000 A with 1 braid(s) 1250 A with 2 braid(s) 1350 A with 2 braid(s) 1600 A with 2 braid(s) 2000 A with 2 braid(s) 2500 A with 3 braid(s) 3200 A with 3 braid(s) 4000 A with 4 braid(s) 5000 A with 5 braid(s)
Connections - terminals	M10 terminals, 8 x , 10 mm
Location of connection	Side
Width	100 mm
Net weight	2.8 kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	110.0 cm
Package 1 Width	60.0 cm
Package 1 Length	10.0 cm
Package 1 Weight	30.0 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile

Circularity Profile	 End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
PVC free	Yes