



Main

Range	Canalis
Product name	KT
Product or component type	Connection adapter
Device short name	KTB
Product compatibility	KHF18 KHF14 KHF16
Range compatibility	Canalis KT trunking Canalis KH trunking
[Ie] rated operational current	1600 A at 35 °C
Polarity	3L + N + PE
Earth conductor	Reinforced
Short-circuit level	Standard version
Length	850 mm

Complementary

Network frequency	50/60 Hz
[Ui] rated insulation voltage	1000 V
Neutral position	Right
Width	600 mm
Height	466 mm
Colour	White (RAL 9001)
Net weight	63 kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	60.0 cm
Package 1 Width	60.0 cm
Package 1 Length	100.0 cm
Package 1 Weight	83.0 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
PVC free	Yes