



Main

| | |
|------------------------------------|------------------------------|
| Range | Canalis |
| Product name | KT |
| Product or component type | Junction block |
| Offer type | Spare part |
| Busbar description | Standard |
| Range compatibility | Canalis KTC |
| Accessory / separate part category | Connection accessory |
| Device application | Joining |
| Material | Copper |
| [Ie] rated operational current | 1600 A with copper |
| Polarity | 3L + N + PER |
| PE conductor | Reinforced |
| lcw short-circuit version | Standard version |
| IP degree of protection | IP55 conforming to IEC 60529 |
| Length | 360 mm |

Complementary

| | |
|--------------------------------|----------------------------|
| Housing material | Polyester film |
| Mounting support | Self-tapping screw |
| [Ue] rated operational voltage | 1000 V |
| Number of circuits | 1 |
| Colour | White (RAL 9001) |
| Width | 140 mm |
| Height | 124 mm |
| Standards | IEC 61439-6 IEC 61439-1 |

Environment

| | |
|-------------------------|------------------------------|
| IK degree of protection | IK08 conforming to IEC 62262 |
|-------------------------|------------------------------|

Packing Units

| | |
|------------------------------|----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 16.4 cm |
| Package 1 Width | 14.0 cm |
| Package 1 Length | 40.0 cm |
| Package 1 Weight | 10.55 kg |

Offer Sustainability

| | |
|--------------------------|---|
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant with Exemptions |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End Of Life Information |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |