




## Main

|                                |                               |
|--------------------------------|-------------------------------|
| Range                          | Canalis                       |
| Product name                   | KT                            |
| Product or component type      | Elbow                         |
| Busbar description             | Standard                      |
| Device short name              | KTC                           |
| Device application             | Change direction              |
| Material                       | Copper                        |
| [Ie] rated operational current | 2500 A at 35 °C               |
| Polarity                       | 3L + N + PER                  |
| Direction change type          | Direction 1: flat to right    |
| Operating angle                | 90 °                          |
| Earth conductor                | Reinforced                    |
| Short-circuit level            | Standard version              |
| Provided equipment             | Trunking unit<br>Joining unit |

## Complementary

|                                          |                                                                                                                                                                                                                                                                                |
|------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Housing material                         | Polyester film                                                                                                                                                                                                                                                                 |
| Contacts material                        | Copper                                                                                                                                                                                                                                                                         |
| [Ue] rated operational voltage           | 1000 V                                                                                                                                                                                                                                                                         |
| Network frequency                        | 50/60 Hz                                                                                                                                                                                                                                                                       |
| [Ui] rated insulation voltage            | 1000 V                                                                                                                                                                                                                                                                         |
| [Icw] rated short-time withstand current | 80 kA                                                                                                                                                                                                                                                                          |
| [Ipk] rated peak withstand current       | 176 kA                                                                                                                                                                                                                                                                         |
| Radiated magnetic field                  | 1.3 µT                                                                                                                                                                                                                                                                         |
| Thermal stress limit                     | 6400000 kA².s                                                                                                                                                                                                                                                                  |
| THDI                                     | 33...100 % 1600 A<br>15...33 % 2000 A<br>0...15 % 2500 A                                                                                                                                                                                                                       |
| Maximum voltage drop                     | <0.0018 V with power factor = 0.8 at 50 Hz with 1A for 100 m long<br><0.0015 V with power factor = 1 at 50 Hz with 1A for 100 m long<br><0.0018 V with power factor = 0.9 at 50 Hz with 1A for 100 m long<br><0.0018 V with power factor = 0.7 at 50 Hz with 1A for 100 m long |
| Neutral position                         | Left                                                                                                                                                                                                                                                                           |
| Standards                                | IEC 61439-6<br>IEC 61439-1                                                                                                                                                                                                                                                     |
| Dimension type                           | Made to measure                                                                                                                                                                                                                                                                |
| Width                                    | 140 mm                                                                                                                                                                                                                                                                         |
| Height                                   | 204 mm                                                                                                                                                                                                                                                                         |
| Length                                   | Direction 1: 301...600 mm<br>Direction 2: 301...1100 mm                                                                                                                                                                                                                        |
| Colour                                   | White (RAL 9001)                                                                                                                                                                                                                                                               |
| Linear load                              | 60 kg/m                                                                                                                                                                                                                                                                        |

## Environment

|                         |                              |
|-------------------------|------------------------------|
| IP degree of protection | IP55 conforming to IEC 60529 |
| IK degree of protection | IK08 conforming to IEC 62262 |
| Derating factor         | 0...35 °C (100 % of In)      |

## Packing Units

|                              |          |
|------------------------------|----------|
| Unit Type of Package 1       | PCE      |
| Number of Units in Package 1 | 1        |
| Package 1 Height             | 20.4 cm  |
| Package 1 Width              | 65.0 cm  |
| Package 1 Length             | 115.0 cm |
| Package 1 Weight             | 107.1 kg |

## Offer Sustainability

|                            |                                                                                                                                 |
|----------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                                                           |
| REACH Regulation           |  <a href="#">REACH Declaration</a>             |
| EU RoHS Directive          | Compliant with Exemptions                                                                                                       |
| Mercury free               | Yes                                                                                                                             |
| China RoHS Regulation      |  <a href="#">China RoHS Declaration</a>        |
| RoHS exemption information |  <a href="#">Yes</a>                           |
| Environmental Disclosure   |  <a href="#">Product Environmental Profile</a> |
| Circularity Profile        |  <a href="#">End Of Life Information</a>      |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins     |