



### Main

Range	TeSys
Device short name	LA9G
Product or component type	Switch module
Quantity per set	Set of 3

### Complementary

Product compatibility	LC1G630...800
Accessory / separate part type	Kit
Maximum [I <sub>e</sub> ] rated operational current	1050 A AC-1 ≤ 440 V at 40 °C 800 A AC-3 ≤ 440 V at 40 °C
Poles description	3P
Connections - terminals	Bolted connection
Height	127.5 mm
Width	284 mm
Depth	202 mm
Net weight	8.5 kg

### Environment

Pollution degree	3 conforming to IEC 60947-1
Operating altitude	3000 m without power derating 5000 m with derating factor
Standards	EN/IEC 60947-4-1 UL 60947-4-1 CSA C22.2 No 60947-4-1 GB/T 14048.4
Ambient air temperature for operation	-25...60 °C
Ambient air temperature for storage	-60...80 °C

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	24.2 cm
Package 1 Width	36.5 cm
Package 1 Length	35.4 cm
Package 1 Weight	3 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#"> REACH Declaration</a>
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	<a href="#"> China RoHS Declaration</a>
RoHS exemption information	<a href="#"> Yes</a>
Environmental Disclosure	<a href="#"> Product Environmental Profile</a>
Circularity Profile	<a href="#"> End Of Life Information</a>
PVC free	Yes
Halogen content performance	Halogen free plastic parts product







