

# Product data sheet

## Characteristics

LA9G4750

Change-over connection bar, for TeSys Giga contactor LC1G115-225, 4 pole



## Main

|                                    |                      |
|------------------------------------|----------------------|
| Range                              | TeSys                |
| Device short name                  | LA9G                 |
| Product or component type          | Set of connections   |
| Accessory / separate part category | Connection accessory |
| Electrical circuit type            | Changeover           |
| Quantity per set                   | Set of 1             |

## Complementary

|                       |               |
|-----------------------|---------------|
| Poles description     | 4P            |
| Product compatibility | LC1G115...225 |
| Range compatibility   | TeSys Giga    |
| Height                | 45 mm         |
| Width                 | 62.1 mm       |
| Depth                 | 302.6 mm      |
| Net weight            | 0.5 kg        |

## Environment

|                                       |   |
|---------------------------------------|---|
| Standards                             | EN/IEC 60947-4-1<br>UL 60947-4-1<br>CSA C22.2 No 60947-4-1<br>GB/T 14048.4  |
| Product certifications                | ABS[RETURN]BV[RETURN]CB[RETURN]CCC[RETURN]CCS[RETURN]CUL[RETURN]EN[RETURN]GL[RETURN]EAC[RETURN]KC[RETURN]LR[RETURN]LR[RETURN]LROS (Lloyds register of shipping)[RETURN]RCM[RETURN]RINA[RETURN]RMRoS |
| Ambient air temperature for operation | -40...60 °C   |
| Ambient air temperature for storage   | -60...80 °C   |
| IP degree of protection               | IP20 conforming to IEC 60529  |
| Operating altitude                    | 3000 m without derating<br>5000 m with derating factor  |

## Packing Units

|                              |           |
|------------------------------|-----------|
| Unit Type of Package 1       | PCE       |
| Number of Units in Package 1 | 1         |
| Package 1 Height             | 9.500 cm  |
| Package 1 Width              | 11.500 cm |
| Package 1 Length             | 35.000 cm |
| Package 1 Weight             | 931.000 g |
| Unit Type of Package 2       | S04       |
| Number of Units in Package 2 | 15        |
| Package 2 Height             | 30.000 cm |
| Package 2 Width              | 40.000 cm |
| Package 2 Length             | 60.000 cm |
| Package 2 Weight             | 15.479 kg |

## Offer Sustainability

|                             |   |
|-----------------------------|---|
| Sustainable offer status    | Green Premium product   |
| REACH Regulation            |  <a href="#">REACH Declaration</a>             |
| EU RoHS Directive           | Compliant with Exemptions   |
| Mercury free                | Yes   |
| China RoHS Regulation       |  <a href="#">China RoHS Declaration</a>        |
| RoHS exemption information  |  Yes   |
| Environmental Disclosure    |  <a href="#">Product Environmental Profile</a> |
| Circularity Profile         |  <a href="#">End Of Life Information</a>       |
| PVC free                    | Yes   |
| Halogen content performance | Halogen free plastic parts product  |





